



Industrial Display Product Roadmap



CPT Customers



ADVANTECH

Panasonic

FEC



LEXMARK[™]

XPLORE
TECHNOLOGIES

TWINHEAD

Getac

ARBOR

Accton

EBN
EBN Technology Corp.

WINMATE



PromptControl
Display Solution / System Engineering



ADVANPOS
AdvanPOS Technology Co., Ltd.

IEI
IEI Integration Corp.
威強電工業電腦

TVM

msi



OMRON

Product Applications



POS



Medical



Panel IPC



Rugged Tablet



ATM



Door Phone



Bathroom TV




Pachinko



OA/IA Product List

Aspect Ratio	wu6	Model	Type	Resolu.	Lum.	Tcon	LED Driver	NTSC	Interface	Op. Temp.	LED Lifetime	Reverse Scan	FRC	Note
4:3/ 5:4	5.7"	057VC01	TN	640x480	220	v	v	50%	TTL	-30~85℃	30,000	Yes	No	
	8"	080XA12	TN	1024x768	300	v	x	50%	LVDS	-10~50℃	10,000	Yes	Yes	
	10.4"	104EA03	HFFS	960x1280	800	v	x	70%	LVDS	-30~85℃	50,000	Yes	8bit	ES
		104XA02	TN	1024X768	400	v	x	47%	LVDS	-20~70℃	30,000	No	No	
	12.1"	121MQ01	TN	800x600	450	v	v	60%	LVDS	-30~80℃	50,000	Yes	Yes	CS
		121XA01	TN	1024x768	600	v	v	70%	LVDS	-20~70℃	50,000	Yes	Yes	ES
	15"	150XQ01	TN	1024x768	450	v	v	60%	LVDS	-30~80℃	50,000	Yes	Yes	
		150XQxx	TN		600	v	v	72%	LVDS	-30~80℃	50,000	Yes	Yes	Planning
	17"	170EC01	TN	1280x1024	450	v	v	72%	LVDS	-20~70℃	50,000	Yes	Yes	CS
		170ECxx	TN		600	v	v	72%	LVDS	-20~70℃	50,000	Yes	Yes	Planning
	19"	190EB01	TN	1280x1024	450	v	v	72%	LVDS	-30~80℃	50,000	Yes	Yes	ES
	21.3"	213QAxx	HFFS	2048x1536	700	v	x	sRGB 100%	LVDS	0~60℃	50,000	Yes	10bit	Medical, Planning

- All models in this page are square-pixel type.



OA/IA Product List

Aspect Ratio	Size	Model	Type	Resolu.	Lum.	Tcon	LED Driver	NTSC	Interface	Op. Temp.	LED Lifetime	Reverse Scan	FRC	Note
8:3/ 15:9/ 16:9/ 16:10	5"	050LA0A	TN	800x480	500	v	x	50%	TTL	-20~70℃	10,000	Yes	Yes	SP
	7"	070LD0D	TN	800x480	500	v	x	45%	TTL	-30~85℃	30,000	Yes	Yes	SP
		070LF0B	TN	800x480	450	v	x	50%	TTL	-20~70℃	30,000	Yes	Yes	
		070LFA1	TN	800x480	450	v	x	50%	TTL	-30~85℃	30,000	Yes	Yes	
		070NJ05	TN	1024x600	500	v	x	50%	LVDS	-20~70℃	30,000	Yes	Yes	
		070NQ08	HFFS	1024x600	600	v	x	50%	LVDS	-20~70℃	30,000	Yes	Yes	CS
		070WP0B	HFFS	800x1280	380	v	x	60%	MIPI	0~50℃	10,000	Yes	Yes	SP
		070WP0F	HFFS	800x1280	450	v	x	60%	LVDS	-20~70℃	50,000	Yes	Yes	SP Kickoff
		080LJ01	TN	800x480	450	v	x	50%	TTL	-20~70℃	30,000	Yes	Yes	
	8"	080LJA1	TN	800x480	600	v	x	50%	TTL	-30~85℃	30,000	Yes	Yes	
		080NA12	TN	1024x600	600	v	x	50%	LVDS	-20~70℃	30,000	Yes	Yes	
		080WK05	HFFS	1280 x 720	500	v	v	70%	LVDS	-20~70℃	20,000	Yes	Yes	SP CS Stage
		080WQ05	HFFS	800x1280	350	v	x	58%	MIPI	-20~60℃	15,000	Yes	Yes	SP
	8.8"	088WA01	HFFS	1280x480	500	v	x	70%	LVDS	-20~70℃	30,000	Yes	Yes	SP



OA/IA Product List

Aspect Ratio	Size	Model	Type	Resolution	Lum.	Tcon	LED Driver	NTSC	Interface	Op. Temp.	LED Lifetime	Reverse Scan	FRC	Note
8:3/ 15:9/ 16:9/ 16:10	9"	090NA06	TN	1024x600	500	v	x	50%	LVDS	-20~70℃	30,000	Yes	Yes	
		090WK05	HFFS	1280 x 720	500	v	v	70%	LVDS	-20~70℃	30,000	Yes	Yes	SP CS Stage
	10.1"	101ND06	TN	1024x600	500	v	x	50%	LVDS	-20~70℃	30,000	Yes	Yes	
		101WH32	TN	1280x800	450	v	x	50%	LVDS	-20~70℃	15,000	No	Yes	SP
		101WM01	HFFS	1280 x 720	550	v	v	70%	LVDS	-20~70℃	30,000	Yes	Real 8 bits	SP ES Stage
		101WRxx	HFFS	800x1280	350	v	x	50%	MIPI	-10~60℃	15,000	Yes	Yes	SP Planning
		101FP07	HFFS	1920x1200	450	v	x	50%	eDP	-10~50℃	15,000	Yes	Yes	SP
		101FP0A	HFFS	1920x1200	700	v	x	50%	LVDS	-10~50℃	TBD	Yes	Yes	Kickoff
	10.2"	102ND01	TN	1024x600	400	v	v	70%	LVDS	-20~70℃	20,000	No	Yes	CS Stage
	10.3"	103WA01	HFFS	1280x480	600	v	x	70%	LVDS	-20~70℃	30,000	Yes	Yes	SP
	21.5"	215FA06 (FOB)	TN	1920x1080	--	v	v	70%	LVDS	0~50℃	--	No	Yes	SP FOB
		215FA07	TN	1920x1080	250	v	v	70%	LVDS	0~50℃	30,000	No	Yes	SP Planning
	27.6"	276FP01	HFFS	1920x360	1000	v	v	70%	LVDS	-20~70℃	70,000	Yes	Yes	SP ES



Displaying your vision!